

IT300 Cutter Suction Dredger 绞吸式挖泥船

• General Description :

Cutter Suction Dredger is self-propelled or non self-propelled, portable cutter suction dredger. Hull can be dismantled and re-assemble easily with box structure . equipped with horizontal shifting devices, cutter ladder lifting devices, spud devices, deck crane and so on. Widely used in sand-excavating, river dredging, desilting, reclamation for channels and land, port construction, etc.

◆ 概 述:

◆ 我们生产的挖泥船是自航或非自航式的,移动式绞吸挖泥船,船体采用可拆卸式和箱体结构,配备横移绞车,绞刀架提升装置,定位桩,甲板吊等等,广泛适用于挖沙、河道清淤、航道维护和拓宽、疏浚、吹田造地、港口建设等。

Advantage :

Reliable and Efficient

The key component like engine, pump and hydraulic system are adopted the international brand.

- Tested in pool before delivery
 Quality testing for each dredger before delivery to ensure all function working properly.
- Services --experienced engineers to guide installing and training local workers. 24/7 technical support standby. Free spare parts in the first year, low cost for services.
- Dismantled and easy transport

◆ 优势:

◆ 可靠高效-关键设备国际品牌

- ◆ 出厂前测试池测试
- ◆ 售后服务-工程师现场安装培训。全天候技术支持,第一年免费更换零件,随后成本价更换并提供服务。
- ◆ 可拆卸便于运输









- 4				
IT300 (12 inch 1500m³/h)				
	Dredger LOA	总长		25.0m
	Hull size(L×B×H)	船体尺寸		19.0×6.2×2.0m
	Main pontoon(L×B×H)	主浮体尺寸		11.6×2.2×2.0m
	Side pontoon (L×B×H)	边浮体尺寸		16.0×2.0×2.0m
- 1	Structure	结构		box-strucure
	Main engine brand & power	主机品牌/总功率		Cummins/522kw
L	Auxiliary engine brand& power	辅机品牌/功率		
	Harbour generator	停泊发电机		Cummins/20kw
	Total power	整船功率		542kw
	Dredging pump	挖泥泵		Warman Technology
	Discharge pipe inner Dia.	排管内直径		300mm
	Head	扬程		40m
	Max. dredging depth	最大挖深		10m
	Water flow	清水流量		1500m³/h
	Solid sand capacity	泥沙产量		300m³/h
	Discharge distance	排距		1200m
	Cutter head Dia.	绞刀头直径		1350mm
	Cutter power	绞刀功率		60kw
	Draught	吃水		1.3m
	Displacement	排水量		116T
	Hydraulic control system	液压控制系统		PLC Siemens
	Wire rope pulling force (Lifting winch)*Quantity 钢丝绳拉力(提升绞车)&数量		50KN *1	
	Wire rope pulling force (Traversing winch)*Quantity 钢丝绳拉力(横移绞车)&数量		50KN *2	
	Operation room		Adjustable cha	ir, movable side-window, air condition,
	操作室		PLC sys	tem, signal lights and floodlights
	Total weight	总重		70T
	Total fuel oil consumption	总油耗		78L/H